



4432

32" COLOR FLAT PANEL DISPLAY

FEATURES:

- LED Backlight
- Anti-Reflective Protective Viewing Window
- Wide Viewing Angle in All Directions
- High Resolution 1920×1080
- Convenient Side Controls

SPECIFICATIONS:

Active Display Area: 28.03" x 15.81"
(712 mm x 401 mm)

Pixel Pitch: 0.3637 mm

Brightness: 350 cd/m² (Typical)

Viewing Angle: ±88° All Directions (Typical)

Contrast Ratio: 3000:1 (Typical)

Response Time: 6.4 ms (Typical/GTG)

Display Colors: 16.7 Million

Input Signal: **Analog video:** 0.7V p-p/75 Ω
(input impedance)
Sync: Separate sync. TTL level

Input Interface: HD-15 (VGA), DVI-D

Video Input Impedance: 75 Ohms

Native Resolution: 1920 x 1080

Resolutions Supported: 640 x 480 @ 60-75 Hz
800 x 600 @ 60-75 Hz
1024 x 768 @ 60-75 Hz
1280 x 1024 @ 60-75 Hz
1366 x 768 @ 60 Hz

Display Controls: OSD Membrane Controls

Temperature: **Operating:** (Sea Level): 8°C to 50°C, MIL-STD-810E Method 501.3/502.3, Procedure II
Storage: -20°C to + 60°C, MIL-STD-810E, Method 501.3/502.3, Procedure 1

Humidity: **Operating/Storage:** 5 to 95% RH Non-condensing MIL-STD-810E Method 507.3, Procedure I

Shock: MIL-STD-901D, Grade B Class I, Type A

Vibration: 1.0G RMS 10–200Hz, 10 min, 1 time each axis X, Y, Z (Non- Operational)

Power: **Supply:** 100-240/ VAC Auto Ranging
Frequency: 50-60Hz
Power: 100 Watts (Typical)

Dimensions: 32.5"W x 20"H x 4.11" DP

Weight: 43 lbs